

MSDS Document

Product IRM 903

DISTRIBUTED BY
R. E. CARROLL, INC.
1570 NORTH OLDEN AVENUE
TRENTON, NJ 08638-3204
609-695-6211 / 800-257-9365

1. Chemical Product and Company Identification

Trade Name of this Product IRM 903

Synonyms: 2915-00

MSDS ID 2915-00

Manufacturer

Calumet Lubricants Company

2780 Waterfront Pkwy E. Suite 200

Indianapolis, IN 46214

Contact Name

Anne Goldsmith

Phone Number

(317) 328-5660

Emergency Phone

CHEMTREC (800) 424-9300

unused

6/14/02

Health:	0
Fire:	1
Reactivity:	0
Specific	

2. Composition and Information on Ingredients

Ingredient	CAS Number	Weight %	ACGIH TLV	PEL	STEL
Heavy Hydrotreated Naphthenic Distillates (petroleum)	64742-52-5	100.0 %	5	5	

3. Hazard Identification

Hazards

This product is a clear, pale-straw to water-white, viscous liquid. It has a light petroleum odor.

This product is slightly combustible (Flammability Class IIIB) but will burn. The flash point is >201°F and autoignition temperature is 650°F. Heated product will produce colorless vapors. Heated vapors in the presence of an ignition source can be explosive if confined. When burned, the product will produce carbon monoxide and other asphyxiants during combustion.

DO NOT REMOVE
"Master Conv"

Prolong unprotected exposure to this product will cause skin irritation. Material splashed in eyes will irritate tissues. Gently flush material from eyes with clean water. Remove product soaked clothing and wash with mild soap.

As with any petroleum product, avoid mixing this product with strong oxidizers.

Carcinogen listed by: National Toxicology Program (NO)

I. A. R. C. (NO)

OSHA (NO)

ACGIH (NO)

This product does not require a cancer hazard warning in accordance with the OSHA Hazard Communication Standard.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Personnel with pre-existing skin disorders should avoid contact with this product.

Health studies have shown that many petroleum hydrocarbons and synthetic lubricants pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

4. First Aid Information

First Aid Measures

EYES

If splashed into eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call a physician.

SKIN

In case of skin contact, remove any contaminated clothing and wash skin with soap and water. Launder or dry-clean clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury. Prolonged or repeated skin contact may cause skin irritation.

INGESTION

Product is practically non-toxic. Do not induce vomiting. Obtain emergency medical attention.

INHALATION

Vapor pressure is very low. Vapor inhalation under ambient conditions is normally not a problem. If overcome by vapor from hot product, immediately remove from exposure and call a physician. If breathing is irregular or has stopped, start resuscitation; administer oxygen, if available. If overexposed to oil mist, remove from exposure until excessive oil mist condition subsides.

5. Fire Fighting Measures

Flash Point	430
FP Method	ASTM D92

FLAMMABLE PROPERTIES

FLASH POINT: >325°F >163°C COC ASTM D92

AUTO IGNITION: >650°F >343°C

FLAMMABILITY CLASS: IIIB

6. Accidental Release Measures

Release Measures

Extinguish any open flames and remove heat sources.

This material will float on water and will be transported by stormwater runoff. Spills to the ground should be immobilized and removed immediately. Spills to watercourses such as stormdrains, sewers, ditches, streams, ponds, etc. must be contained with dikes, dams, floating booms, pads, etc. as appropriate. Remove trapped product immediately.

Spills that enter a waterbody must be immediately reported to the USEPA's National Response Center at (800)546-2972.

Check with your local and state regulators regarding their reporting requirements.

Cleanup personnel should wear appropriate personnel protective equipment including impervious clothing, rubber boots, gloves, and splash goggles.

7. Handling and Storage

Handling and Storage

HANDLING AND STORAGE PRECAUTIONS

Keep away from flames, sparks or hot surfaces. Never use a torch to cut or weld on or near container. Empty oil containers can contain explosive vapors. NFPA Class IIIB storage. Wash thoroughly after handling.

WORK/HYGIENIC PRACTICES

Wash hands with soap and water before eating, drinking, smoking or use of toilet facilities. Do not use gasoline, solvents, kerosene, or harsh abrasive skin cleaners for washing exposed skin areas. Take a shower after work if general contact occurs. Remove oil-soaked clothing and launder before reuse. Launder or discard contaminated shoes and leather gloves.

"EMPTY" CONTAINER WARNING

"Empty" containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Do not attempt to refill or clean containers since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged and promptly returned to a drum reconditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

For work on tanks refer to Occupational Safety and Health Administration regulations, ANSI Z49.1, and other governmental and industrial references pertaining to cleaning, repairing,

welding, or other contemplated operations.

8. Exposure Controls and Personal Protection

Exposure/PPE/Heavy

VENTILATION

Use local exhaust to capture vapor, mists or fumes, if necessary. Provide ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air. No smoking, or use of flame or other ignition sources.

EYE/FACE PROTECTION

Use safety glasses or splash goggles when eye contact may occur. Have suitable eye wash water available.

SKIN PROTECTION

Avoid prolonged and/or repeated skin contact. If prolonged contact cannot be avoided, wear protective impervious gloves and clothing. Acceptable materials for gloves are polyvinyl chloride; neoprene; nitrile; polyvinyl alcohol; viton.

RESPIRATORY PROTECTION

Normally not required if adequate ventilation. If occupational exposure limits are exceeded wear NIOSH/MSHA approved apparatus.

OTHER/GENERAL PROTECTION

If there is a likelihood of splashing, an oil resistant clothing should be worn. Never wear oil soaked clothing. Launder or dry clean before wearing. Discard oil soaked shoes. Affix warning labels on containers in accordance with 29 CFR 1910.1200 (Hazard Communication Standard).

INGREDIENT NAME BY VOLUME	EXPOSURE LIMITS	CONCENTRATION PERCENT
------------------------------	-----------------	--------------------------

Heavy Hydrotreated Naphthenic Distillates (petroleum)
100.0
CAS NUMBER: 64742-52-5 Exposure Limits: OIL MIST
OSHA PEL MIST 5 MG/M3 8 HRS
ACGIH TLV MIST 5 MG/M3 8 HRS

9. Physical and Chemical Properties

Product CAS Number 64742-52-5
Specific Gravity 0.9206
Density lbs/Gal. 7.68

APPEARANCE: Clear, pale straw colored, viscous liquid

ODOR: Light bland petroleum

PHYSICAL STATE: Liquid

BOILING POINT: IBP >480°F IBP >249°C

MELTING POINT: N/A
VAPOR PRESSURE: <0.0001 mm Hg @ 20°C
VAPOR DENSITY: Greater than air
SPECIFIC GRAVITY: 0.9206 Water = 1
MOLECULAR WEIGHT: N/A
SOLUBILITY (H2O): negligible in water
VOLATILE ORGANIC COMPOUNDS (VOC) CONTENT: N/A
VISCOSITY: 150 SUS at 100°F
Typical IP 346: N/A

Physical data may vary slightly to meet specifications.

10. Stability and Reactivity

Stability/Reactivity

STABILITY: Stable. Will not react violently with water.

CONDITIONS TO AVOID

Sources of ignition.

INCOMPATIBLE MATERIALS

Strong oxidizers such as liquid chlorine, concentrated oxygen, sodium hypochlorite, calcium hypochlorite, etc., as this presents a serious explosion hazard.

HAZARDOUS DECOMPOSITION PRODUCTS

Combustion may produce carbon monoxide and other asphyxiants.

HAZARDOUS POLYMERIZATION: will not occur

11. Toxicological Information

Toxicological

ACUTE STUDIES

Product has a low order of acute and dermal toxicity, but minute amounts aspirated into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death.

EYE EFFECTS

Product contacting the eyes may cause eye irritation.

SKIN EFFECTS

Prolonged or repeated skin contact with this product tends to remove skin oils, possibly leading to irritation and dermatitis; however, based on human experience and available toxicological data, this product is judged to be neither a "corrosive" nor an "irritant" by OSHA criteria.

ACUTE ORAL EFFECTS

Product has a low order of acute and dermal toxicity, but minute amounts aspirated into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death.

ACUTE INHALATION EFFECTS

Product has a low order of acute and dermal toxicity, but minute amounts aspirated into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death.

In accordance with the current OSHA Hazard Communication Standard criteria, this product does not require a cancer hazard warning. This is because the product is formulated from base stocks which are severely hydrotreated, severely solvent extracted, and/or processed by mild hydrotreatment and extraction. Alternatively, it may consist of components not otherwise affected by IARC criteria, such as atmospheric distillates or synthetically derived materials, and as such is not characterized by current IARC classification criteria.

12. Ecological Information

Ecological Info

If applied to leaves, this product may kill grasses and small plants by interfering with transpiration and respiration. This product is not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water. Product may be moderately toxic to amphibians by preventing dermal respiration. This product may cause gastrointestinal distress to birds and mammals through ingestion during pelage grooming.

This product is rapidly biodegradable. Biodegradation is possible within 90 to 120 days in aerobic environments at temperatures above 70°F (21°C).

13. Disposal Considerations

Disposal

Product, as supplied, does not meet the characteristics of a hazardous waste as defined in 40 CFR 261.21-24. If mixed with other products, waste mixture must be characterized. DO NOT dispose of this product in drains or storm sewers. DO NOT dispose of this product in a landfill without prior solidification. Waste product should be recycled. Consider waste brokering.

14. Transportation Information

Transport Info

PROPER SHIPPING NAME: Not regulated by DOT

HAZARD CLASS: Not applicable

DOT IDENTIFICATION NUMBER: N/A

DOT SHIPPING LABEL: Not regulated by DOT

15. Regulatory Information

Compliance

U.S. FEDERAL REGULATORY INFORMATION

SARA 302 Threshold Planning Quantity: NOT APPLICABLE

SARA 304 Reportable Quantity: NOT APPLICABLE

SARA 311 Categories: Immediate (Acute) Health Effects --N

Delayed (Chronic) Health Effects --Y

Fire Hazard	--N
Sudden Release of Pressure	--N
Reactivity Hazard	--N

EPA/TSCA Inventory: The components of this product are listed on the EPA/TSCA inventory of chemicals.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA): No chemicals in this product are subject to the reporting requirements of CERCLA.

SARA TITLE III - SECTION 313 SUPPLIER NOTIFICATION

No chemicals in this product exceed the De Minimus reporting level established by SARA Title III, Section 313 and 40 CFR 372.

EUROPEAN (ECC) REGULATORY INFORMATION

This product is listed on the European Inventory of Existing Commercial Substances.

CANADIAN REGULATORY INFORMATION

This product is listed on the Canadian (DSL) Domestic Substances List.

WHMIS Classification: NOT CONTROLLED

16. Other Information

Disclaimer

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information contained herein is based upon data believed to be reliable and reflects our best professional judgment. Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein and assume no responsibility regarding the suitability of this information for the user's intended purpose or for the consequence of its use. Each individual should make a determination as to the suitability of the information for his/her particular purpose(s).

Superceeds MSDS Dated: 02/21/01